

STROOMAGGREGAAT GE 6500 DS/GS - DES/GS

- Yanmar dieselmotor
- Handstart (DS/GS)
- Elektrische start (DES/GS)
- Driefase synchrone generator
- Uitgangen: 1 x 400V 16A 3P+N+T CEE
1 x 230V 16A 2P+T CEE
- ELCB-GFI (aardlekschakelaar)
- Zekeringautomaat
- Buizenframe
- Onderstel (optie)
- Voldoet aan EG veiligheids- en geluidsnormen



| Standaard Uitrusting | | | | | | | | | |
|----------------------|----------------------------|-------------|------------------|--------------------|--------------------------|----------------------------|------------|--|------------------------------------------------------------|
| | Diesel engine | Air cooling | Manual recoil ** | Electric Starter * | Oil pressure Indicator * | Battery charge indicator * | Hour-meter | | |
| Opties | | | | | | | | | |
| | Synchronous alternator | Compound | Sockets 3~ | Sockets 1~ | ELCB-GFI | Circuit Breaker | Voltmeter | | |
| | ● 400V plug ● 230V plug | | | | ● Earthing kit | | | | ● Battery holder complete with battery ● Trolley CTM6/2 |

* only GE6500 DES/GS
** only GE6500 DS/GS

Uitvoering op verzoek ● Schuko sockets

Technische gegevens

| A.C GENERATOR – 50 Hz | GE 6500 DS/GS | GE 6500 DES/GS |
|-----------------------------------------|------------------------------------------------------------------|----------------|
| | Three-phase synchronous alternator, self-excited, self-regulated | |
| * Stand-by three-phase power | 6.5 kVA (5.2 kW) / 400 V / 9.4 A | |
| * P.R.P. three-phase power | 5.7 kVA (4.6 kW) / 400 V / 8.2 A | |
| * P.R.P. single-phase power | 4 kVA / 230 V / 17.4 A | |
| Cos φ | 0.8 | |
| Insulation class | H | |
| * Output powers according to ISO 8528-1 | | |

| MOTOR | GE 6500 DS/GS | GE 6500 DES/GS |
|----------------------------------|-----------------------------------------------|----------------|
| | 4-stroke diesel, air cooled, direct injection | |
| Model | Yanmar L100N | |
| * Stand-By net power | 6.5 kW (8.8 HP) | |
| * P.R.P. net power | 5.7 kW (7.7 HP) | |
| Cylinders/ Displacement | 1/ 435 cm ³ | |
| Speed | 3000 rpm | |
| Fuel consumption (75% of P.R.P.) | 1.2 l/h | |
| * Powers according to ISO 3046-1 | | |

| ALGEMENE SPECIFICATIES | GE 6500 DS/GS | GE 6500 DES/GS |
|-------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|----------------|
| Tank capacity | 5.5 l | |
| Running time (75% of P.R.P.) | 4.6 h | |
| IP protection degree | IP 23 | |
| *Dimensions LxWxh (mm) | 900x550x622 mm | |
| *Dry weight | 107 Kg | 108 Kg |
| ** Acoustic power LwA (pressure LpA) | 99 dB(A) (74 dB(A) @ 7m) | |
| * Dimensions and weight without trolley/trailer. ** For indoor use / For fixed installation only, in compliance with Directive 2000/14/EC | | |

Model- en specificatiewijzigingen voorbehouden