

## STROOMAGGREGAAT GE 6500 SX/GS EAS

- Yanmar dieselmotor
- EV motorbewaking
- Electric start
- Enkelfase synchrone generator
- Uitgangen: 1 x 400V 16A 3P+N+T CEE  
1 x 230V 16A 2P+T CEE
- ELCB-GFI (aardlekschakelaar)
- Zekeringautomaat
- Super geluidgedempt
- Onderstel (optie)
- Compact, stil en robuust
- Betaalbare topkwaliteit, ideaal voor aannemerij



Standaard Uitrusting											
	Diesel engine	Air cooling	Electric starter	Battery 12 V	Engine protection	Oil pressure shut down	Low fuel shut down	Battery charge indicator	Hour-meter	Central lifting eye	
Opties											
	Synchronous alternator	Compound	Sockets 3~	Sockets 1~	ELCB-GFI	Circuit Breaker	Voltmeter	Ready for EAS/TCM	Local/remote start selector		
Uitvoering op verzoek	<ul style="list-style-type: none"> <li>● 400V plug</li> <li>● 230V plug</li> </ul>			<ul style="list-style-type: none"> <li>● Automatic transfer unit (AMF) EAS 15D-806</li> <li>● Remote control</li> <li>● Earthing kit</li> </ul>				<ul style="list-style-type: none"> <li>● Exhaust extension</li> <li>● Trolley CTM2</li> <li>● Road trolley CTV4</li> </ul>			

### Technische gegevens

### GE 6500 SX/GS EAS

#### A.C GENERATOR – 50 Hz

#### Three-phase synchronous alternator, self-excited, self-regulated

\* Stand-by three-phase power

6.5 kVA (5.2 kW) / 400 V / 9.4 A

\* P.R.P. three-phase power

5.7 kVA (4.6 kW) / 400 V / 8.2 A

\* P.R.P. single-phase power

4 kVA / 230 V / 17.4 A

cos φ

0.8

Insulation class

H

\* Output powers according to ISO 8528-1

#### MOTOR

#### 4-stroke diesel, air cooled, direct injection

Model

Yanmar L 100 N

\* Stand-By net power

6.5 kW (8.8 HP)

\* P.R.P. net power

5.7 kW (7.7 HP)

Cylinders/ Displacement

1/435 cm<sup>3</sup>

Speed

3000 rpm

Fuel consumption (75% of P.R.P.)

1.2 l/h

\* Powers according to ISO 3046-1

#### ALGEMENE SPECIFICATIES

Tank capacity

23 l

Running time (75% of P.R.P.)

19 h

IP protection degree

IP 23

\*Dimensions LxWxh (mm)

1020x645x930 mm

\*Dry weight

200 kg

\*\*Measured acoustic power L<sub>WA</sub> (pressure L<sub>pA</sub>)

91 dB(A) (66 dB(A) @ 7m)

\*\*Guaranteed acoustic power L<sub>WA</sub> (pressure L<sub>pA</sub>)

92 dB(A) (67 dB(A) @ 7m)

\* Dimensions and weight without trolley/trailer. \*\* Acoustic power according to European Directive 2000/14/EC