

LASAGGREGATEN TS 200 DES/EL

- Yanmar dieselmotor - luchtgekoeld
- Asynchrone generator
- Aardlekschakelaar
- Electronische lasstroom regeling (170A)
- Ook geschikt voor cellulose elektroden
- Buizenframe
- Onderstel CTM (optie)
- Afstandbediening (optie)
- Voldoet aan EG veiligheids- en geluidsnormen
- Hulpstroom (6 kVA) beschikbaar tijdens lassen



Standaard uitrusting



Diesel engine	Air cooling	Electric starter	C.B Thermal shut off	Battery charger indicator	Hour Meter	Low oil pressure			
Welding current electr. regulation	Asynchronous alternator	Socket 400V CEE	Socket 230V CEE	Socket 110 V	Ground fault interrupter	Thermal shut off	Ready for TC		

Opties



- Plug 400V 16A 3PNT (T)
- Plug 230V 16A 2PT (M)
- Plug 48V 32A 2PT (M)
- Welding cables K190 (10+8m, 35mm²)
- Welding cables K200 (20+15m, 35mm²)
- Remote controla TC2 with cable 20m
- Remote controla TC2/50 with cable 50m
- Trolley CTM6/2
- PB3 Battery holder Complete with battery
- Earthing kit MT10

Technische gegevens

TS 200 DES/EL

D.C. LASSEN

Current range, continuous	20 - 170A
Open circuit voltage	65 V
Duty cycle	170A - 60%, 130 A - 100%
Electrode diameter	2 - 4 mm

A.C. GENERATOR

50 Hz, asynchronous, three-phase, self-excited, self-regulated, brushless

Three-phase generation	6 kVA / 400 V / 8,7 A
Single-phase generation	5 kVA / 230 V / 21,7 A
Single-phase generation	2.5 kVA / 110 V / 22.7 A
Duty cycle	100%
Insulating class	H

On request other voltages and frequencies (60 Hz)

MOTOR

Diesel, 4-stroke, air cooled

Type	YANMAR L 100AE
Output *	6.5 kW (8.8 HP)
Speed	3000 rpm
Displacement / Cylinders	406 cm ³ / 1
Fuel consumption	245 g/kWh

* Maximum output (not overloadable) according to ISO 3046/1

ALGEMENE SPECIFICATIES

Tank capacity	5.5 l
Running time (at duty cycle 60%)	4.5 h
Protection	IP 23
Dimensions LxIhx (mm) *	900x550x622
Weight *	133 kg
Noise level	99 LWA(74 dB(A) - 7 m)

* Dimensions and weight are inclusive of all parts without optional CTM

Model- en specificatiewijzigingen voorbehouden